

# CLACK CE CONTROL VALVE

Customisable control valve with programmable dealer details feature, developed by Ecosoft and produced by Clack Corporation

## Key Features:

1. Multilingual Menu
2. Easy Automatic Programming
3. Professional Programming for Advanced Users.
4. Auto Diagnostic Mode for Error Detection.
5. Salt and Service Maintenance Alarm.
6. Dealer Contact Information.
7. Display Backlight with Energy Saving Mode.
8. Additional Connection of External Clack Motorized Devices.
9. Relay Outputs.



Specifications				
Valve	WS1CE	WS125CE	WS15CE	WS2CE
Inlet/Outlet Fittings	1"	1¼"	1.5"	2"
Valve Materials	Noryl	Noryl	Brass	Brass
Service Flow Rate (@ 1 bar drop)	6.15	7.7	13.6	26.1
Backwash Flow Rate (@ 1.7 bar drop)	6.15	7.2	11.4	18.1
Cycles	Up to 9			
Regeneration	Downflow / Upflow			
Operating Pressure	1.4 – 8.6			
Operating Temperature	4 – 43°C			
Cycles or Operation				
1. Backwash	1 – 120 min			
2. Regen. Draw/Slow Rinse	1 – 120 min			
3. Fast Rinse	1 – 180 min			
4. Regenerant Refill	0.1 – 100 kg			
5. Service	1 – 480 min			
Compatible With				
Sodium Chloride, Potassium Chloride, Potassium Permanganate, Sodium Bisulfite, Chlorine and Chloramines				