

## AquaSorb<sup>®</sup> CX-MCA

catalytic granular coconut shell based activated carbon

### Features and Benefits

- Catalytic activity
- Large and extensive internal pore structure
- Optimized density
- Maximum hardness
- Low dust and turbidity
- Excellent adsorption capacity
- High volume activity
- Rapid dechlorination
- Low filtered water turbidity

### Typical Applications

- Residential water treatment systems - Point of Entry (POE) / Point of Use (POU)
- Beverage production
- Protection of ion exchange resins from chloramines

### Available Particle Sizes

- 12x40 mesh (0.425 - 1.70 mm)
- other granulations available upon request

### Certifications and Approvals

- AWWA B604-96
- EN12915
- NSF Std. 61

### Standard Packaging

- 25 kg bag (55 lb)
- 500 kg bulk bag (1100 lb)



The polyethylene valve bag from Jacobi sets the standard in the industry for clean, durable and safe handling.

AquaSorb<sup>®</sup> CX-MCA is a catalytic, high activity granular activated carbon manufactured by steam activation of select coconut shell charcoal. The catalytic activity of this activated carbon makes it highly effective for the removal of chloramines and hydrogen sulfide from potable water. Its large micropore volume makes it particularly well suited for the removal of low molecular weight organic compounds and their chlorinated by-products such as chloroform and other trihalomethanes (THMs). An important feature of this material is its superior mechanical hardness and the extensive dedusting during its manufacture ensures an exceptionally clean activated carbon product.



AquaSorb<sup>®</sup> CX-MCA is an activated carbon with a catalytic activity that is required for liquid phase application involving oxidation, reduction, and decomposition.

### Specification

Iodine number	min. 1000 mg/g
Moisture content (as packed)	max. 5%
Total ash content	max. 4%
Ball-pan hardness	min. 98%
CTC activity	min. 50%
Catalytic activity	min. 20°C

### Typical Properties

Surface area (BET)	1060 m <sup>2</sup> /g
Apparent density	514 kg/m <sup>3</sup>
Bed density, backwashed and drained	437 kg/m <sup>3</sup>
pH	10

Jacobi Carbons reserves the right to modify specifications without prior notice. To obtain a full sales specification with test methods, please contact your nearest Jacobi Carbons office.

#### CORPORATE OFFICE

##### Sweden

Jacobi Carbons AB  
Bredbandet 1, Varvsholmen  
SE-392 30 Kalmar

Tel: +46 480 417550  
Fax: +46 480 417559  
info@jacobi.net  
www.jacobi.net

#### SALES OFFICES

##### Germany

Jacobi Carbons GmbH  
Feldbergstrasse 21  
D-60323 Frankfurt/Main

Tel +49 69 719107-0  
Fax +49 69 719107-20  
infode@jacobi.net

##### United States

Jacobi Carbons, Inc.  
1518 Walnut Street, 18th Floor  
Philadelphia, PA 19102

Tel: [215] 546-3900  
Fax: [215] 546-9921  
infous@jacobi.net

##### United Kingdom

Jacobi Carbons Ltd.  
Croft Court, Moss Estate  
Leigh, Lancs, WN7 3PT

Tel: +44 1942 670 600  
Fax +44 1942 670 605  
infouk@jacobi.net

##### Malaysia

Jacobi Carbons (Asia) Sdn Bhd  
1-04-18, Krystal Point Corporate Park  
Jalan Tun Dr. Awang  
11900 Bayan Lepas, Penang

Tel: +60 4 643 9828  
Fax: +60 4 644 3928  
infoasia@jacobi.net



# Jacobi

THE CARBON COMPANY

#### SALES OFFICES (cont.)

##### Finland

Jacobi Carbons AB (SS)  
Ruoholahdenkatu 8  
SF-00180 Helsinki

Tel: +358 9 643602  
Fax: +358 9 642900  
infofin@jacobi.net

##### Switzerland

Jacobi Carbons AG  
Rheinweg 5  
CH-8200 Schaffhausen

Tel: +41 52 647 30 00  
Fax: +41 52 647 30 09  
infoch@jacobi.net



Certified to ANSI/NSF Std. 61



Polyethylene valve bags of  
25 kg (55 lb) net weight on  
500 kg (1100 lb) pallets



Polypropylene liner-free  
FIBCs (super sacks) of  
500 kg (1100 lb) net weight

**CAUTION** Activated carbon is a strong oxidizing agent and can remove oxygen from air under wet or humid conditions. Care should be taken when entering confined spaces where wet activated carbon is present. Ensure the use of correct breathing apparatus. Material Safety Data Sheets should be consulted for further details on procedures in the event of contact with activated carbon.

**NOTICE** Due to the progressive nature of Jacobi Carbons Group and the continually improving design and performance of our products, we reserve the right to change product specifications without prior notification. The information contained in this datasheet is intended to assist a customer in the evaluation and selection of products supplied by Jacobi Carbons. The customer is responsible for determining whether products and the information contained in this document are appropriate for customer's use. Jacobi Carbons assumes no obligation or liability for the usage of the information in this datasheet, no guarantees or warranties, expressed or implied, are provided. Jacobi Carbons disclaims responsibility and the user must accept full responsibility for performance of systems based on this data.

**WORLDWIDE DISTRIBUTORS** A diverse network of agents, strategically located around the world. Please contact any Jacobi Carbons office to locate your nearest distributor. AquaSorb, EcoSorb, GoldSorb, ColorSorb, DioxSorb, AddSorb and Jacobi are registered trademarks of Jacobi Carbons. © Jacobi Carbons, 2007.

DSE-ASCXMCA-A-0707

